



seating inc.

Brisa® | Original & Distressed



533-4487 Sage



533-5747 White




533-3019 Birch



533-3863 Cream



533-3864 Desert Clay




535-3137 Saddle*



533-3823 Aztec



533-3825 Canyon




533-3913 Truffle



533-2694 Night Navy



533-5820 Quicksilver



535-3974 Steerhide*



533-5749 Black Onyx

Brisa® | Fresco



544-7313 Sea Glass



544-5711 Coconut



544-3100 Whey



544-3102 Grotto



544-3105 Sepia



544-8210 Tangerine



544-1341 Paprika



544-1349 Elderberry



544-3197 Patina



544-4474 Waxed Canvas



544-2565 Dungaree



544-5752 Flint



544-5754 Peppercorn

Ultraleather® | Promessa®




363-9387 Moroccan Fig



363-3152 Parchment



363-3036 Linen



363-3462 Woodpecker



363-3224 Brown Earth




363-7273 Aspen Green



363-5258 Sun Shower



363-3145 Bronze



363-1387 Dogwood



363-2604 Stone Blue



363-7309 Malibu



363-5818 Ash



363-5845 Ebony

Ultraleather® | Pro



554-2711 Blueberry



554-0008 White Wash



554-3803 Parfait



554-3352 Shore



554-3444 Toasted Bagel




554-2661 Blue Bird



554-9336 Aubergine



554-1329 Rhubarb



554-3376 Dark Chocolate



554-3087 Woodcres



554-5648 Cloud



554-5626 Char



554-5618 Dark Knight

*Denotes Distressed

SPECIFICATIONS

	Brisa® Original Brisa® Distressed Breathable technology	Brisa® Fresco Antimicrobial protection Breathable technology	Ultraleather® Promessa® Antimicrobial protection	Ultraleather® Pro Antimicrobial protection Ink and denim resistant
COMPOSITION:	100% POLYURETHANE SURFACE	100% POLYURETHANE SURFACE	100% POLYURETHANE SURFACE	100% POLYURETHANE SURFACE
WEIGHT:	APPROX. 9.3 OZ. PER SQUARE YARD APPROX. 315 GRAMS PER SQUARE METRE	APPROX. 9.3 OZ. PER SQUARE YARD APPROX. 315 GRAMS PER SQUARE METRE	APPROX. 12 OZ. PER SQUARE YARD APPROX. 410 GRAMS PER SQUARE METRE	APPROX. 9.7 OZ. PER SQUARE YARD APPROX. 330 GRAMS PER SQUARE METRE
THICKNESS:	APPROX. 1.0 MM	APPROX. 1.0 MM	APPROX. 1.1 MM	APPROX. 0.95 MM
WIDTH:	54 INCHES / 137 CM	54 INCHES / 137 CM	54 INCHES / 137 CM	54 INCHES / 137 CM
CHARACTERISTICS				
ABRASION: (MEETS OR EXCEEDS)	ASTM D4157 / 300,000 DOUBLE RUBS* BS 2543 / 160,000 RUBS** *WYZENBEEK **MARTINDALE	ASTM D4157 / 300,000 DOUBLE RUBS* BS 2543 / 160,000 RUBS** *WYZENBEEK **MARTINDALE	ASTM D4157 / 400,000 DOUBLE RUBS* BS 2543 / 180,000 RUBS** *WYZENBEEK **MARTINDALE	ASTM D4157 / 500,000 DOUBLE RUBS* BS 2543 / 200,000 RUBS** *WYZENBEEK **MARTINDALE
AIR PERMEABILITY:	ASTM D737	ASTM D737	NA	NA
ANTIMICROBIAL:	NA	ASTM E2180	ASTM E2180	ASTM E2180
SOUND ABSORPTION:	ASTM C423	ASTM C423	NA	NA
HYDROLYSIS:	14+ WEEKS ASTM D3690-02 SECT. 6.11 (HYDROLYTIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)	14+ WEEKS ASTM D3690-02 SECT. 6.11 (HYDROLYTIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)	14+ WEEKS ASTM D3690-02 SECT. 6.11 (HYDROLYTIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)	14+ WEEKS ASTM D3690-02 SECT. 6.11 (HYDROLYTIC STABILITY) ISO 1419 METHOD C (ACCELERATED AGEING)
ADHESION OF COATING:	ASTM D751	ASTM D751	ASTM D751	ASTM D751
TEAR STRENGTH:	ASTM D2261	ASTM D2261	ASTM D2261	ASTM D2261
BREAKING STRENGTH:	ASTM D5034	ASTM D5034	ASTM D5034	ASTM D5034
COLORFASTNESS				
CROCKING:	AATCC 8, CLASS 5 WET & DRY	AATCC 8, CLASS 5 WET & DRY	AATCC 8, CLASS 5 WET & DRY	AATCC 8, CLASS 5 WET & DRY
LIGHT:	AATCC 16.3, 200 HOURS, GRADE 4-5 ISO 105 - B02 : 1999 GRADE 7/8	AATCC 16.3, 200 HOURS, GRADE 4-5 ISO 105 - B02 : 1999 GRADE 7/8	AATCC 16.3, 200 HOURS, GRADE 4-5 ISO 105 - B02 : 1999 GRADE 7/8	AATCC 16.3, 200 HOURS, GRADE 4-5 ISO 105 - B02 : 1999 GRADE 7/8
F/R RATING (HFR FREE)				
F/R RATING:	ASTM E84 (ADHERED) CLASS A CA TB 117-2013 PASS FMVSS 302 & 95/28 ANNEX IV PASS NFPA 260 CLASS 1 UFAC CLASS 1	ASTM E84 (ADHERED) CLASS A CA TB 117-2013 PASS FMVSS 302 & 95/28 ANNEX IV PASS NFPA 260 CLASS 1 UFAC CLASS 1	ASTM E84 (ADHERED) CLASS A CA TB 117-2013 PASS FMVSS 302 & 95/28 ANNEX IV PASS NFPA 260 CLASS 1 UFAC CLASS 1	ASTM E84 (ADHERED) CLASS A CA TB 117-2013 PASS FMVSS 302 & 95/28 ANNEX IV PASS NFPA 260 CLASS 1 UFAC CLASS 1

* CAN BE TREATED TO MEET FAR SPECIFICATIONS.

* THESE FABRICS, WHEN TREATED AND/OR USED WITH OTHER COMPATIBLE FURNITURE COMPONENTS, HAVE BEEN SHOWN TO PERFORM WELL UNDER THE FIRE TEST CONDITIONS OF CALIFORNIA TECHNICAL BULLETIN 133, ASTM E 84 (UNADHERED), BS 5852 SOURCE 5 ("CRIB 5"), BS 7175, BS 5867 PART 2 TYPE B, IMO A.652(16) AND NFPA 701.

Maintenance & Care Instructions

- Clean with soap and water, or alcohol-based cleaners like Fantastik® and Formula 409®
- Disinfect using a 1:5 bleach/water solution
- Ultraleather® | Pro - for ink and tough stains, clean using isopropyl/rubbing alcohol
- Rinse all cleaning solutions with clean water

Earth Friendly

- **GREENGUARD Certified**
 - Meets stringent VOC emission standards
 - Promotes healthier indoor air quality
 - Contributes towards satisfying credits under LEED® and level®, BIFMA
- Compliant with Prop 65
- Less than 100 ppm of antimicrobial treatment⁺
- No Conflict Minerals
- No Flame Retardants (ex. Halogenated, Brominated)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No Plasticizers, Heavy Metals, Stabilizers, Phthalates or Bisphenol A (BPA)
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

⁺Denotes Fresco, Pro, and Promessa®

Seating Inc.

50 North State Street

Nunda, NY 14517

T 585.468.2875 | F 585.468.2804

www.seatinginc.com



6/16

www.ultrafabricsllc.com

Ultrafabrics® and logo, Ultraleather®, Brisa®, Ultratech®, and Promessa® are trademarks of Ultrafabrics, LLC. Made in Japan.

